# Installation Instructions

## LED CUTOFF ARCHITECTURAL WALL PACK

### **ARWP Series**









The luminaire must be installed by a qualified electrician in accordance with applicable federal, state, and local laws and codes. Installation requires knowledge of luminaire electrical systems and installer should be familiar with the operation of this product. If not qualified, do not attempt installation; contact a qualified electrician. Manufacturer assumes no responsibility for the improper installation of this luminaire. When installing the fixture, drilling may damage luminaire wiring and electrical parts. Check for wiring and components in enclosure before drilling. Turn OFF power before installation or attempting any maintenance.

To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects. When installing this kit, drilling may damage luminaire wiring and electrical parts. Check for wiring and components in enclosure before drilling.



WARNING Risk of Burn.

Disconnect power and allow fixture to cool before handling or servicing.



### WARNING Risk of Personal Injury.

Wear gloves or proper handling protection to prevent cuts or abrasions when handling and maintaining this product. This equipment may have sharp edges. To reduce the risk of death, personal injury or property damage from fire, electric shock, falling parts, cuts/abrasions, and other hazards read all warning and instructions included with and on the fixture box and all fixture labels.

Avoid direct eye exposure to the light source while it is on.

#### NOTICE

- Green ground screw provided in proper location. Do not relocate.
- Minimum 90°C supply conductors.
- Suitable for wet location.
- Specifications and dimensions subject to change without notice.

Contact manufacturer with any questions or concerns regarding installation of this luminaire.






# Installation Instructions


# **LED Cutoff Architectural wall pack**

## A: Adjusting CCT and Wattage.


1. Loosen the screws and remove the cover from fixture.



2. Loosen the screws and carefully detach the LED reflector assembly. And adjust the DIP switches to the desired settings.




3. Reattach the LED reflecor assembly and the cover. Restore power and check that the fixture is functioning properly.




#### **B: Standard wall mount**


1. Loosen the two set screws found on the cover of the housing.



2. Remove the guick mount bracket from the fixture and attach it to the junction box (not included) with the appropriate hardware.




- 3. Follow the Wiring Diagram to connect the fixture leads to the supply leads. If dimming is not required, make sure to cap off the dimming wires. Tuck any extra length of wire into the junction box.
- 4. Lift the fixture and tilt slightly toward the quick bracket. Hook the fixture housing onto the quick mount bracket as shown. Take care not to pinch any wires.




# Installation Instructions

# **LED Cutoff Architectural wall pack**

5. Tighten the two set screws to secure the fixture housing to the quick mount bracket.



6. Restore power and check that the fixture is working properly.



#### NOTE:

Fixture must be sealed where it contacts the mounting surface with a silicone sealant (Not included).

## Wiring Diagram:



