



PROJECT

TYPE

DATE

ITEM NO.

NOTE

## DIE-CASING LED LINEAR HIGH BAY

## HBDC Series

Die-Cast High Bay

### DESCRIPTION

HBDC is a super compact design with die-cast aluminum housing, lumen and CCT selectable features, dual lensed linear high bay. It delivers 20250 to 48000lms, PIR and microwave sensors ready and supports easy install at field, no wiring required. Standard 90°90° beam angle lens with superior optical control delivers optimal performance while reducing high angle glare, 110°110°, 65°65°, 45°90° beam angle lens options for different application and layout requires.



### APPLICATION

Various commercial and industrial applications with high ceilings: warehouse, factories, workshops, retail, grocery, gymnasiums, exhibition halls.

### SPECIFICATION FEATURES

#### Construction

Rigid, low-profile, compact, die-cast aluminum housing provides added protection for LED components and optimal performance. With socket for PIR/Microwave sensor options, Lens, LED module and driver are replaceable.

#### Mounting

Comes standard with V-hook and chain for suspension mount. Various mounting options available: Surface mount, air craft cable suspended, pendant mount.

#### Finish

Highly reflectivity finish. Baked white paint, applied after fabrication.

#### Electrical

Luminaire utilizes long life, high efficacy LEDs and a highly efficient, reliable LED driver. 3 level wattage and CCT selectable switches for lumens output and 3500/4000/5000K, 120-347V operating voltage, 0-10V dim-to-off comes standard, with 3.5 mm phono jack receptacle as controls ready for DC sensors that supports field installed.

#### Optics

Dual polycarbonate lensed and 90°90° beam angle as standard, narrow, medium, wide distribution lens options.

#### Certifications / Regulatory

cULus listed for damp locations, FCC part 15 class A compliant. DLC5.1 Premium listed.

#### Warranty

7-year limited warranty. See complete warranty terms for details.

### Quick Ship Product

HBDC-(215/180/135)/8A  
HBDC-(320/275/235)/8A

## ORDERING INFORMATION

Sample Number: HBDC-(215/180/135)/8A

Series	Lumen Package		CRI	CCT	Input Voltage
HBDC - Die-Casting LED High Bay	(215/180/135) - 215/180/135W, 32250/27000/20250lm	(320/275/235) - 320/275/235W, 48000/41250/35250lm	8 - 80CRI	A - CCT Adjustable (5000/4000/3500K)	(Blank) - 120-347V 480 - 277-480V

Optics	Control Option	Emergency Backup
(Blank) - Diffuser with 90x90° W110 - Diffuser with 110x110° N65 - Diffuser with 65x65° N45 - Diffuser with 45x90°	OS - Bi-level dimming PIR sensor and daylight switch, field install in 5 seconds (Required RC-100 Sensor Configuration Tool) OS-BLE - Wireless Bluetooth with PIR sensor AWN-R - Lutron Athena wireless node integral fixture control (RF only) AWN-S - Lutron Athena wireless node integral fixture control (RF with daylight and occupancy sensing) *  *Recommended to be used at heights of 8-12 feet for optimal coverage.	EM25W - 25W constant power in emergency mode** EM40W - 40W constant power in emergency mode EM40W-480V - 40W constant power in emergency mode, AC input 480V***  **25W emergency backup is only suitable for 215W fixture, not for 320W fixture. ***EM40W-480V only suitable for suspension, surface mount, not available for pendant mount.

Assembly in Mexico	Accessories
TAA - Assembly in Mexico	HBDC-WG-215W - Wire Guard for 215W HBDC-WG-320W - Wire Guard for 320W HB-ACC - 3.3' Aircraft cable suspension kit HBDC-SMK - Surface Mount Kit  HBDC-EM-SMK - Surface Mount Kit for installed EM version HBDC-PMK - Single-point pendant mount kit for 3/4" NPT stems (stems not provided) HBDC-EM-PMK - Single-point pendant mount kit for 3/4" NPT stem for installed EM version (stem not provided)

SUMMARY


Input Voltage	120-347V
Input Frequency	50/60 Hz
Power Factor	> 0.9
THD (Max.)	< 20%
Efficacy	150 LPW
Controls/ Dimming	Full Range 0-10V dimming standard
Dimming Range	10-100%
CRI	>80
CCT	3500/4000/5000K Adjustable
Operating Temp.	-40°F~131°F (-40°C~55°C)
Surge Protection	6KV
IK Rated	IK06
Rated Life	70,000 hours

ENERGY PERFORMANCE DATA

Part No.	Rated Wattage (W)	Delivered Lumens (lm)	Efficacy (lm/W)
HBDC-(215/180/135)/8A	215/180/135	32250/27000/20250	150
HBDC-(320/275/235)/8A	320/275/235	48000/41250/35250	150

\*The delivered lumens above are based on 4000K.  
 \*\*Default setting at time of shipping are highest wattage and highest CCT.

OPTICS





Note: Photometric layout for reference only.

Snap-on screwless design for easy optic swap



PHYSICAL PARAMETERS

DIMENSION



**CONTROLS (Field install in 5 seconds)**

OS:MMS-DC-PIR4T

OS-BLE: MMS-PIR4T-BLE-SR



RC-100



AWNDR: (Athena wireless node RF only)




AWNS: (Athena wireless node with daylight and occupancy sensing)




**ACCESSORIES**

Suspension mount (Default and included)




HB-ACC




HBDC-SMK




HBDC-PMK




Suspension mount with EM



Surface mount with EM



Pendant mount with EM



HBDC-WG-XXXW

